

# Dalton Direct Tile - 20 mil Series Vinyl Plank

## TECHNICAL DATA

### **SPECIFICATION**

Size:	4" x 36" and 6" x 36"
Overall Thickness:	2.0mm
Wear layer Thickness:	20 mil
Wear layer Material:	Vinyl / WearGUARD
Construction Material:	Laminated Vinyl
Pieces Per Carton:	4" - 36/carton and 6" - 24/carton
Square Feet Per Carton:	36
Carton Weigh:	27 lbs.

### **PLANK**

### **Commercial Test Information**

Slip Resistance:	ADA Approved
ASTMD-2047-93:	ADA Approved
Static Load:	2000 psi
ASTM F970:	Passes
Resistance to Taber Abrasion:	3000cy.
ASTMD-1044-94:	19.8 milligram weight loss
Resistance to Impact:	Passed
FED.STD.501 Method 3311:	4 of 4 Impacts

Critical Radiant Flux ASTM E 648-94A, NEPA 253, FTM No.372, NBSIR 75-950	Class I
---	---------

Smoke Density Test ASTM E 662	450
-------------------------------	-----

Surface Burning Characteristics of Burning Material ASTM E-84-94	Class A
---	---------

Maintenance:	Normal Commercial Maintenance Required. See Instructions For Details.
Warranty:	15 Year Commercial, Lifetime Residential
Vinyl:	Asbestos Free
Adhesive:	Use Taylor 2091 or Mapei Eco 350
Chemical Testing:	Contact us For Complete Testing Information
Acoustical Tests Available:	Contact us For Complete Testing Information